

Valve Description Chart



Valves	½" Water Inlet	¾" Water Inlet	Type T, P ou T/P	Required minimum wall thickness	Connection Type	Water outlet	Maximum flow rate
XX51 XX71 (PRO)	X		P	2X3	NPT or Sweat, SPEX, EX	1+1	22 L/min 5,8 gpm (US)
XX23 XX93 (PRO) 2-way	X		T/P (coaxial)	2x3	NPT or Sweat, SPEX, EX	2	24 L/min 6,3 gpm (US)
XX45 XX95 (PRO) 3-way	X		T/P (coaxial)	2x3	NPT or Sweat, SPEX, EX	3	24 L/min 6,3 gpm (US)
XX46 4-way	Copper	SPEX EX	T/P (coaxial)	2x3	NPT	4	38 L/min 10 gpm (US)
XX83 4-way		X (direct)	T/P (coaxial)	2x4	NPT	4 (2+2)	76 L/min 20 gpm (US)
Genius Shower 2-way	X		T/P	2x3	NPT	2	19 L/min 5 gpm (US)
CSTM77	X (extern)		T	2x3	NPT	1	21 L/min 5,5 gpm (US)
CSTM81	X (extern)		T	2x3	NPT	2	18,4 L/min 4,8 gpm (US)

T: Thermostatic
P: Pressure balance
T/P: Thermostatic/
Pressure balance

SPEX: PEX
EX: Expansion PEX